

- Surface mountable
- External weatherproof
- Pro-linear lens optimises light distribution
- Cable entry on each end with BESA in rear and cable channel for through wiring
- End entry clips to accept mini trunking and improve aesthetics
- Compatible with Protec DigiLite® 500 Automatic Addressable Testing System

Bulkhead Luminaire



The Bulkhead 'BH' luminaire is suitable for external emergency applications, including defined escape routes. The Bulkhead 'BH' luminaire is IP65 rating making it suitable for external use with the added benefit of a screw fixing diffuser for added security.

The Protec Pro-linear lens system optimises light distribution to maximise luminaire spacing and reduce installation costs.

NOTES:

Prefix DL/ for addressable emergency lighting interface for use with Protec DigiLite® 500 Automatic testing system.

Prefix ST/ for Self Test luminaire.

Exit Legend: The Protec self adhesive European format Exit Legend can be fitted to this luminaire. Protec Ref: Self/Euro

- Available in maintained, non-maintained, central battery and mains only versions.
- Compatible with Protec DigiLite® 500 Automatic Addressable Testing system.
- Available as Protec 'Self Test' emergency lighting luminaire.
- Manufactured to EN60598:2.22.
- Clip on diffuser and gear tray for easy installation.
- Screw fixed diffuser for added security.
- Self adhesive exit legend available.

Technical Specification

SELF CONTAINED LUMINAIRES				
Sales Order Code	Mode	Emergency Lamp Output	Normal Lamp Output	Weight (Kg)
BULKHEAD WEATHERPROOF 'BH'				
BH/NM3	NM	100 LUMEN	N/A	1.20Kg
BH/M3	M	100 LUMEN	400 LUMEN	1.60Kg

Mode NM = Non Maintained M = Maintained

Input Voltage 230v +/- 10% 50 Hz
 Input Current 25mA - Non Maintained, 175mA - Maintained
 Emergency Duration 3 Hours
 Environment 0°C to 25°C
 Lamp Type 8 Watt

CENTRAL BATTERY LUMINAIRES				
Sales Order Code	Emergency Lamp Output	Central Battery Power Input AC(VA)	Central Battery Power Input DC (Watts)	Weight (Kg)
BULKHEAD WEATHERPROOF 'BH'				
BH/24	320 LUMEN	10.5	10.5	1.1Kg
BH/50	360 LUMEN	11.5	11.5	1.1Kg
BH/110	360 LUMEN	10	10	1.1Kg

MAINS ONLY LUMINAIRES				
Sales Order Code	Normal Lamp Output	Input Watts Without PFC	Input Watts With PFC	Weight (Kg)
BULKHEAD WEATHERPROOF 'BH'				
BH/240	400 LUMEN	38	15	1.2Kg

Input Voltage 220/240v 50Hz. Suffix /PFC for power factor correction to 0.85

Dimensions

