

- Squeeze grip operation
- Non-magnetic model supplied with blue handle
- CO<sub>2</sub> harmless to machinery
- 2kg model supplied with frost free horn as standard
- Polished aluminium model has clear polyester powder coating
- Complete with wall bracket



Stored Pressure

These extinguishers have all the same efficient fire-fighting properties for flammable liquids as the stored pressure models but as cartridge operated units. These are ideal for marine use.

| Type                         | CO <sub>2</sub><br>ALUMINIUM | CO <sub>2</sub><br>ALUMINIUM | CO <sub>2</sub><br>POLISHED<br>ALUMINIUM | CO <sub>2</sub><br>ALUMINIUM<br>NON-<br>MAGNETIC |
|------------------------------|------------------------------|------------------------------|--|--|
| <b>Capacity (Kg)</b>         | <b>2</b>                     | <b>5</b>                     | <b>2</b>                                 | <b>2</b>   |
| Fire rating                  | 34B                          | 70B                          | 34B                                      | 34B  |
| Height (mm)                  | 490                          | 750                          | 490                                      | 490  |
| Cylinder diameter (mm)       | 117                          | 152                          | 117                                      | 117  |
| Overall width (mm)           | 180                          | 310                          | 180                                      | 180  |
| Filled weight (kg)           | 4.91                         | 11.43                        | 4.91                                     | 4.91   |
| Range of throw (m)           | >4                           | >4                           | >4                                       | >4   |
| Duration of discharge (secs) | 8                            | 14                           | 8  | 8  |
| Working pressure (at 20°C)   | 56 bar                       | 56 bar                       | 56 bar                                   | 56 bar   |
| Temperature range (°C)       | -30 to 60 °C                 | -30 to 60 °C                 | -30 to 60 °C                             | -30 to 60 °C                                     |
| BS EN3 approved              | yes                          | yes                          | no                                       | yes  |
| MED approved                 | no                           | yes                          | no                                       | no   |
| Part Number                  | 9705/00                      | 9706/00                      | 9705/06                                  | 9705/65  |
| Model Number                 | FPC2SC                       | FPC5C                        | FPC2SC                                   | FPC2SC   |