

Saturn Luminaire

- Available in White, Chrome & Brass effect

- Diffuser is easily removed with special lift up clip assembly

- IP65 Rated

- Compatible with Protec DigiLite® 500 Automatic Addressable Testing System



Saturn range of luminaires available in white, chrome and brass effect.

The diffuser has an 'opal' finish and is easily removed with the special lift-up clip assembly.

The luminaire is IP65 rated, supplied with a pre-fitted gasket and a suitable installation kit.

The Saturn is available in a wide range, from the 16 & 28 watt 2D mains, to the self-contained 3 hour duration of the maintained and non-maintained fittings.

Protec also offer a 'PL' range of slave luminaires to run from our 24, 50 and 110 volt central battery systems.

For applications requiring a dual fitting, Protec offer a 28 watt 2D via 240V mains with a PL5, 7 or 9 watt from the 24, 50 or 110 volt central battery unit.

Finally to complete the range, Protec offer the addressable fittings with a choice of 16 or 28 watt 2D lamp.

Technical Specification

| SATURN SELF CONTAINED LUMINAIRES | | |
|--|------------------|--|
| Stock Code | Sales Order Code | Description |
| N 69-222-12 | SA/282D/M3 | Maintained 3 hour 28 watt 2D, in white. |
| N 69-224-14 | SA/282D/NM3 | Non-Maintained 3 hour 28 watt 2D, in white |
| Suffix/BP: brass effect finish. Suffix/CH: chrome effect finish. | | |

| SATURN CENTRAL BATTERY LUMINAIRES | | |
|--|------------------------|--|
| Stock Code | Sales Order Code | Description |
| Upon Request | SA/PL*24/50/110 | PL version to run from the central battery unit. |
| Upon Request | SA/28/240/PL*24/50/110 | 28w 2D mains with the PL Lamp via central battery unit |
| * Select option of PL5/PL7/PL9 & voltage required. Suffix/BP: brass effect finish. Suffix/CH: chrome effect finish. | | |

| SATURN MAINS ONLY LUMINAIRES | | |
|--|------------------|-----------------------------------|
| Stock Code | Sales Order Code | Description |
| N 69-219-09 | SA/162D/240 | Mains only, 16 watt 2D, in white. |
| N 69-220-10 | SA/282D/240 | Mains only, 28 watt 2D, in white. |
| Suffix/BP: brass effect finish. Suffix/CH: chrome effect finish. * Prefix AD/ For Addressable E.L. Interface for use with DL500 automatic testing system. | | |

Dimensions (mm)

